

## iQ500, Built-in double oven, Stainless steel NB535ABS0B



Shorten your cooking time thanks to fast preheat.

- ✓ fast preheat: reach the required cooking temperature sooner.
- ✓ lightControl: intuitive operation thanks to the illuminated dial.
- ✓ ecoClean Plus: effortless cleaning thanks to a special coating of the rear wall that self cleans
- ✓ 3D hotAir: perfect baking results on up to 3 shelves thanks to innovative heat distribution.

### Features

#### Technical Data

Color / Material Front : Stainless steel  
 Design : Built-in  
 Integrated Cleaning system : No  
 Dimensions of the product (mm) : 717 x 594 x 550  
 Dimensions of the packed product (HxWxD) (mm) : 790 x 690 x 660  
 Control Panel Material : Glass  
 Door Material : Glass  
 Net weight (kg) : 46.641  
 Usable volume of cavity (l) : 47  
 Heating Types : Conventional heat, Full width grill, Hot Air, Hot air grilling  
 Oven control : mechanical  
 Number of interior lights : 1  
 Approval certificates : CE, VDE  
 EAN code : 4242003803264  
 Energy efficiency : A  
 Energy consumption per cycle conventional (2010/30/EC) : 0.84  
 Energy consumption per cycle forced air convection (2010/30/EC) : 0.71  
 Energy efficiency class (2010/30/EC) - cavity 2 : B  
 Energy consumption per cycle conventional - cavity 2 (2010/30/EC) : 0.83  
 Energy efficiency index (2010/30/EC) : 94.7  
 Energy efficiency index cavity 2 (2010/30/EC) : 120.3  
 Connection rating (W) : 5600  
 Current (A) : 25  
 Nominal power (kW) : 220-240  
 Frequency (Hz) : 50  
 Plug type : fixed connection, no plug

### Included accessories

- 2 x combination grid
- 1 x universal pan

### Optional accessories

- |          |                                       |
|----------|---------------------------------------|
| HZ915003 | Glass roasting dish, 5,4 L            |
| HZ636000 | Glass pan                             |
| HZ634000 | Baking and roasting grid (standard)   |
| HZ625071 | Grill tray, anthracite enamelled      |
| HZ538000 | varioClip rail                        |
| HZ531010 | Baking tray, non-stick ceramic coated |
| HZ531000 | Baking tray, grey enamelled           |



## iQ500, Built-in double oven, Stainless steel

### NB535ABS0B

#### Features

##### Design

- White display with blue indicator lights
- Bar handle
- lightControl: intuitive operation thanks to the illuminated dials

##### Main Lower oven

- Oven capacity: 47 litre
- 1 interior halogen light
- Smooth enamelled oven interior, Removable wire shelf support rails
- Drop down oven door
- Heating-up indicator
- Control panel lock
- Cavity with shelf support rails

##### Cleaning

- EcoClean Direct : back panel
- Full glass inner door

##### Programmes/functions

- 5 heating methods: 3D hot air, conventional top & bottom heating, hot air grilling, full width grill, Hotair gentle
- fast preheat function

##### Secondary top oven

- Cavity volume: 34 l
- Smooth enamelled oven interior, Removable wire shelf support rails
- 1 interior halogen light

##### Cleaning

- EcoClean Direct :side liners, back panel, ceiling
- Full glass inner door

##### Programmes/functions

- Oven with 4 heating methods: conventional oven, Large-area grill, Small area grill, bottom heat

##### Accessories

- 2 x combination grid, 1 x universal pan
- Cavity with shelf support rails

##### Performance/technical information

- Energy efficiency rating (acc. EU Nr. 65/2014): A
- Energy consumption per cycle in conventional mode: 0.84 kwh
- Energy consumption per cycle in fan-forced convection mode: 0.71 kwh
- Number of cavities: Main cavity
- Heat source: electrical
- Cavity volume: 47 litre capacity
- Energy efficiency rating (acc. EU Nr. 65/2014): B
- Energy consumption per cycle conventional mode: 0.83 kwh
- Number of cavities: Top Cavity
- Heat source: electrical
- Cavity volume: 34 l
- Nominal voltage: 220 - 240 V
- Appliance dimension (hwxwd): 717 mm x 594 mm x 550 mm
- Please refer to the dimensions provided in the installation manual


**iQ500, Built-in double oven, Stainless steel  
NB535ABS0B**

Dimensioned drawings

measurements in mm  
If the appliance will be installed underneath a hob, the following worktop thicknesses (including substructure if necessary) must be taken into account.

Hob type	min. worktop thickness	
	fitted	flush
Induction hob	39	40
Full-surface induction hob	49	50
Gas hob	29	40
Electric hob	29	32

measurements in mm  
Installation with a hob



A: Recessed depth 29-50 mm. See hob dimensional drawing.  
B: Min. distance:  
Induction hob: 5 mm  
Gas hob: 5 mm  
Electric hob: 2 mm

measurements in mm

